

## **COSMOFEN 60** special cleaner

### APPLICATION FIELD

**COSMOFEN 60** is used as mild smelling, fast drying special cleaner in industry and handcraft.

Because of its good compatibility with a lot of different lacquered surfaces\*, **COSMOFEN 60** is highly suitable for a lot of plastic- and metal processing fields.

**COSMOFEN 60** is used for powder-coated and anodized aluminium and PUR profiles in specialized companies.

**COSMOFEN 60** removes dust, adhesive remainders from protection foils, wax pencil, rubber traces, fresh PUR-foam and fresh remainders of sealing compounds, as well as tar- and bitumen splashes.

**COSMOFEN 60** is used for the cleaning before the bonding and in order to remove not hardened up reminders of different adhesive systems..

### TECHNICAL DATA

BASIS	mixed aliphatic hydrocarbons, free of aromatic substances and free of chlorinated hydrocarbons.		
DENSITY	according to EN 542 at +20°C	approx.	0,71 g/cm <sup>3</sup>
MINIMUM TEMPERATURE FOR APPLICATION		from	+5 °C
FLASH POINT			-14 °C
IGNITION TEMPERATURE			+260 °C

### WORKING INSTRUCTIONS

The surfaces to be cleaned must be dry and free from dust. The cleaning is effected with dry, not staining cotton or cellulose cloths.

#### \* Important advices:

\* Usually, lacquered surfaces are not dissolved by **COSMOFEN 60**, but we recommend you to carry out your own preliminary tests, because of the multitude of used kinds of surfaces and lacquer formulas.

\* While cleaning powder-coated surfaces, no colour pigments should appear on the used cloth; this would mean that the powder varnish has not hardened long enough. In such a case, you should immediately ask the person responsible for the powder coating!

### STORAGE

Store original cask tightly closed, dry, at a temperature between +15°C and +25°C, without direct sun radiation.

Can be stored in unopened original casks for approx. 24months.