



POLI-GRIP 400

Product Information

Double-sided adhesive tape for the overlapping connection (splicing) and seaming of banner films.

Safe splicing and seaming of PVC banners with flat and structured surface. Suitable also for the strengthening of loops. Replaces the welding and sewing of banner material.

Extremely high shear and tensile load capacity. Excellent plasticizer resistance. Optimal compound adhesion due to the high thickness of the efficient viscoelastic adhesive. Suitable for applications in interior and exterior areas.

Technical Data

Carrier:	PE-paper with logoprint, white
Adhesive:	Acrylic, modified
Thickness [mm]:	0,40 +/- 0,05
Adhesion [N/cm]:	14,80 +/- 3,00
In dependence on AFERA 5001	
Temperature resistance [°C]:	- 40 °C / + 100 °C Short-term to + 120 °C

Standard Dimensions

38 mm x 25 m With both-sided overlapping liner (joint lift)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH
Zeppelinstraße 17
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0
Fax: +49 (0) 2642 – 9836 37

E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

11/12/2014

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.